

Standard Component Guide



AirXcel MAXX Air Fan



Specs.

Fits 14"x14" roof opening
Over 900 CFM
Operation - Remote or Manual
10 Speed Intake and exhaust fan
12" blade fan
Fuse protected 12v motor

Warranty

2 Year Limited (Lifetime Warranty on Lid)

Benefits

- Built-In Rain Cover to always protect your RV's interior
- Thermostat to control room temperature
- Brings in fresh air and removes hot musty air and odors
- Fan runs with lid closed to circulate air (Ceiling Fan Mode)
- Easy to remove interior insect screen, no tools required
- Twin lifting arms, No more lid fluttering in high winds or when driving
- Flush mounted, easy to clean Keypad, controls fan speed, thermostat, air intake and/or exhaust functions
- Closes securely for a low profile appearance

Barker's VIP 3000 and 3500 Power Jacks

Specs.

3000-24", Black, 24 inch stroke,
3,500 lb. lifting capacity,
2-1/4 inch diameter
outer post VIP Jacks



Warranty

2 Year Extended

Benefits

- 3,000 or 3,500 pound lifting capacity
- Full 18" or 24" stroke with torque limiter protection when fully extended or retracted
- "Nite-Lite" technology to assist when hitching in the dark
- Crank handle for manual override
- Waterproof up and down switch
- Patented built-in level (#6 840 541)
- Attached foot pad
- Powder-coated and plated
- 10-gauge hookup meets RVIA standards

Bulldog Collar-Lok Coupler



Specs.

Ball Size - 2"

Weight rating - 7000 lbs.

Straight Channel

Tongue mount width - 3"

Warranty

1 Year

Benefits

- Easiest to use.
- Strong in both static and dynamic loading conditions.
- Hinged ball socket for easy hook up.
- Clear, visual indication of proper closure.

Contoure Microwave Oven RV950S



Specs.

1.0 cubic foot interior

10.5" glass rotating turntable

120 volt

900 watts

1350 input power

Outside dimensions: 19 1/8" W x 11 1/2" H x 15"D

Dimensions of Cabinet Installation: 20" W x 13 3/8" H x 14- 1/8" D.

Weight - 29 lbs.

Warranty

1 Year

Benefits

6 One Touch Menus make microwave cooking fast

10 Power Levels for different heat levels

Child Safety Lock to prevent unwanted accidents

Jet Defrost for proper food preparation

Interior Oven Light makes it easy to use at night

NEW "Easy Clean" Interior makes cleaning up after easy

Dayton Stainless Steel Kitchen Sink



Specs

Installation Type: Top Mount

Material: Stainless Steel

Gauge: 22 Gauge

Minimum Cabinet Size: 21"

Sink Dimensions: L: 17" W: 19" H: 6-1/8"

Bowl Dimensions: L: 14" W: 14" H: 6"

Drain Size: 3-1/2"

Approximate Shipping Weight: 9 lbs

Warranty

1 Year (Limited)

Benefits

- ADA COMPLIANT: Product is ADA compliant when properly installed.
- TOP MOUNT INSTALLATION: Sink is designed for drop-in installation with a beautifully finished rim to make it a focal point of your kitchen.
- 300 SERIES STAINLESS STEEL: Designed for everyday use.
- QUIET: Sound-deadening material minimizes sound and vibration for a quieter time at the sink.

Delta Stainless Steel Kitchen Faucet



Specs

Spout Height: 7.938"

Spout Reach: 5.375"

Height: 12.313"

Flow Rate: 1.5 GPM

Staggered copper supply lines with 1/2" fitting

Warranty

1 Year (Limited)

Benefits

- Solid brass fabricated faucet body
- Single handle operation
- Spout swivels 360 degrees
- Hot and cold logo on handle to indicate temperature
- ADA compliant - complies with the standards set forth by the Americans with Disabilities Act for kitchen faucets
- Low lead compliant - meeting federal and state regulations for lead content
- CAL Green certified product - using at least 30% less water than standard 2.2 GPM faucets, while still meeting strict performance guide lines

Dexter Axle and Dexter EZ Flex Equalizer



Specs.

Elite I - Single Axle (5000 lbs)

Elite II - Tandem Axle (3500 lbs each = 7000 lbs)

6 Lug Hubs

Heavy Wall 3" Diameter Tube

Warranty

5 Years (Limited) on Axles and 2 Years (Limited) on EZ Flex Equalizer

Benefits

Dexter Axle

Precision machined, forged steel spindles

Precision machined integral cast iron hub/drums

12" x 2" electric brakes, CSA approved at 7000 lbs

High quality alloy steel springs in a variety of capacities

Durable, wear-resistant components

Inner wiring system for easier installation and protection of brake wiring

Dexter EZ Flex

Replaces standard trailer equalizers in leaf spring suspensions

Delivers smoother towing than traditional leaf spring suspensions

Rubber core isolates and absorbs damaging road shocks before they hit the trailer frame and contents

Easy installation - no welding, cutting, or grinding

Includes bolts, shackle links, and rubber equalizers

Dometic 2-Burner Cooktop Stove



Specs

Depth 370 mm

Height 91 mm

Width 480 mm

Weight 4.1 kg

Cut out width 466.00 mm

Cut out depth 358.00 mm

Output cooker plate 1 1.00 kW

Output cooker plate 2 1.80 kW

Gas pressure (DIN732) 30 mbar

Gas category (DIN732) G30 (50% n-butane, 50% i-butane)

Gas consumption cooktop 204.00 g/h

Number of burners 2

Warranty

2 Year Limited

Benefits

- Easy-to-clean detachable pan grids
- Easy temperature control
- Handy safety glass lid that doubles as extra work space when closed

Dometic 13,500 BTU Penguin II A/C



Specs.

Depth 29 "

Height 11 1/4 "

Width 40 1/2 "

Net weight 101 lbs

Input voltage AC 115 V

Input frequency 60 Hz

Cooling capacity (ISO 5151) 3953 W

Power consumption - Cooling mode (ISO 5151) 1731 W

Warranty

2 Year Limited

Benefits

- Improved aerodynamics reduces wind resistance while underway
- High-performance motor and fan for maximum cooling
- Rib-reinforced base pan for strength and durability
- R410A refrigerant is environmentally friendly and releases heat more efficiently
- Effortless, fully automated comfort control
- EPP foam housing reduces weight and improves cooling efficiency

Dometic Toilet 310 Ceramic



Specs.

Dimensions - depth 19"
height 20"
width 15"

Net weight 22.75 lbs.
Color - White

Warranty

2 Years

Benefits

Smooth surface, 100% vitreous ceramic bowl
Cleans with less mess, 360 degree vortex flush pattern
Superior performance, Best in class gravity flush
Cleaning action, powerful swirl-jet cleaning action
The comforts of home, long, full-sized adult seat

Dometic RM 2454 Fridge

Specs.

36-9/16 x 23-11/16 x 24

Weight:

78 lbs

Power:

3-way (LP/120V AC/12V DC)

Color:

Black frame, accepts insert panels



Warranty

3 Years

Benefits

- 3-way operation
- Top mounted controls
- Positive lock door handles
- Adjustable, removable door bins
- One-gallon container shelf storage
- 4.0 Cubic Feet

Dura Faucet Bathroom Sink Faucet/Shower Head

Specs

Weight: 4.69 lbs.
Size (IN): 8 Inch
Spout Type: Pull-Out
Handle Type: Lever
Finish: Nickel Plated
Material: Brass, Zinc, Plastic
Fitting Size: 1/2 Inch NPT



Warranty

1 Year (Limited)

Benefits

RV Pull-Out Faucet Metal Construction with Solid Zinc Lever Handle
1-Hole Installation. Optional Deckplate included Flow
Rate: 2.2 gpm @ 60 psi, 8.3 L/min @ 414 kPa and UPC/CUPC
Certified Long Life Ceramic Disk Valve

Deep Cycle Duralast Marine 12v Batteries



Specs.

Dimensions - length - 10 1/4"
height - 8 7/8"
width - 6 13/16"
Net weight - 47.21 lbs.
Amp Hour - 85
Cold Cranking Amps - 550
Cranking Amps - 685
Reserve Capacity - 140 min.

Warranty

1 Year

Benefits

- Patented grid manufacturing technology produces grids engineered to be more efficient for optimal performance
- Best-in-Class vent caps are engineered to be safer and reduce leakage and corrosion
- Solidium™ welds are designed to stop corrosion and prevent premature failure
- Lifespan™ negative paste is formulated to improve performance and battery life

Elite I Only - Atwood 16,000 BTU Furnace



Specs

Depth (IN): 20 Inch
Type: LP Gas
BTU Level: 16000 BTU
Width (IN): 16-1/2 Inch
Height (IN): 7-3/8 Inch

Warranty

2 Years

Benefits

Our Hydro Flame© brand furnaces are engineered for easy maintenance and superior air delivery- all in a compact package to meet today's demanding space heating needs. Both DC and AC powered versions are available.

Elite II Only – Suburban Furnace NT-20 SQ

Specs

BTUH Input - 19,000

Height - 9 1/2"

Width - 9 3/8"

Depth - 22 1/2"

Voltage - 12 VDC

Amp. Draw - 3.1

Unit Weight - 22 lbs.

Duct Outlet Size - 4" Round

Cut-Out Dimensions - 10 3/16" H x 10 9/16" W



Warranty

2 Years (Limited)

Benefits

These Suburban NTQ Series furnaces are incredibly compact and lightweight. But even with their small size and amp draw, these gas furnaces are capable of heating sizeable living areas quickly and efficiently, with capacities from 16,000 to 19,000 BTUH.

NT-SEQ models are direct discharge furnaces with attractive grilles for zone heating of smaller RVs, trailers, truck campers and even pop-ups. A side duct on SE models is optional. NT-SQ models can be ducted to provide even heat distribution throughout the coach.

Furion DV 3200 Stereo



Specs.

Number Zone Audio Output - 2

Display Type - LCD

Display Size - 4"

Power Output - 4 x 25 Watt (RMS) / 4 x 40 Watt (MAX)

Warranty

1 Year

Benefits

Vibrationsmart Designed and tested for vibration resistance

Climatesmart Designed and tested for extreme climates

Signalsmart Anti-interference static filters

High Definition Multimedia Interface

Bluetooth wireless connectivity

NFC quick-touch device pairing

DVD playback

USB interface (MP3/MP4/WMA)

Front auxiliary in with video support

Front headphone jack

Subwoofer output with optional powered sub

Furriion FEFD22S0A TV



Specs.

Screen Size - 22"

HDTV

USB 2.0 Connections

HDMI and VGA Connections

Warranty

1 Year

Benefits

The ultimate experience: 1080p high definition on an ultra slim LED television, with enhanced audio features and a full spectrum of connectivity options:

Furriion smart link communication

upgraded Furriion speakers and amplifier

Vibrationsmart™ - designed for vibration resistance

Climatesmart™ - tested for extreme climates

ITC RV Fontana Exterior Shower



Specs

5' hose

Cutout: 9" L x 4.5" W

Dimensions: 3" H x 10.5" L x 5.872" W

Warranty

1 Year

Benefits

- Designed for washing down exterior components
- UV-resistant, high-impact plastic
- Includes 5' hose
- Anti-siphon vacuum breaker

Jensen Speakers



Specs.

Size - 5.25"

Weight - 1.2 lbs.

Max Power Handling - 120 Watts

Mounting Hole - 3-3/4"

Warranty

1 Year

Benefits

- Heavy Duty Sealed Speakers
- Max Power Handling: 120 Watts
- Waterproof
- Speaker Color: Black

Michelin LTX M/S2 Tires



Specs

LT225/75/R16

Nitrogen Filled - Tire Pressure remains more stable with temperature changes

Warranty

1 Year

Benefits

Special rubber compounds and better lateral water evacuation helps them stop up to 7 feet shorter than leading competitors' tires.

MaxTouch construction™ maximizes the tire's contact with the road and evenly distributes the forces of acceleration, braking and cornering to deliver miles of driving pleasure.

Tread design features 8% more biting edges than its predecessor for improved grip in snow.

At MICHELIN, we continuously push safety, durability and fuel efficiency, and even more performances, all at the same time and with no trade-offs. That's what we mean by MICHELIN® Total Performance™, which has and will always be our difference on every tire.

Progressive Dynamics Inteli-Power 4000 Series Converter

Specs.



Maximum DC Output Current 45-AMPS
Maximum Continuous Input Power 725
No Load DC Output Voltage 13.6 VDC
No Load Voltage Tolerance +/- .3 VDC
Full Load Output Voltage > 12.6 VDC
Ripple and Noise Voltage < 50 MV RMS
Input Voltage Tolerance 105 - 130 VAC
Input Voltage Frequency 50-60 HZ
Peak Inrush Current 32-AMPS
Input Current at Rated Power ~8.3-AMPS
Efficiency (Typical) > 80%
Reverse Battery Protection YES
Electronic Current Limiting YES
Cooling Fan Auto-variable speed
Back Up Thermal Protection YES
Charge Wizard YES
Storage Temperature -20-80C
Operating Temperature 0-50C
Hipot Voltage Test 1240 V @ INPUT TERMINALS
Over Voltage Protection YES
Under Voltage Protection YES
Weight 5.7 LBS.
Cutout Size 10.75W x 7.25H
Dimensions 12.28W x 8.875H

Warranty

2 Years

Benefits

Industry's smallest all-in-one 45 or 60 Amp distribution panel/converter system.

Available with our exclusive built-in Inteli-Power Converter...

"The most reliable converter in the RV industry."

The converter section is easily accessible from the front.

The AC Distribution Panel is rated for 120 VAC @ 30 Amps with up to 7 branch circuits.

The DC section has 12 branch fuse holders, two wired to accommodate 30 Amp fuses, ten more with a maximum rating up to 20 Amps each. All wire tail connections.

Reverse battery blown fuse indicator.

Shurflo 4008 Water Pump



Specs.

Voltage - 12 VDC

Dimensions: 8.1" x 4.9" x 4.3"

Flow Rate - 3.0 GPM (11.4 LPM)

Amps (Max) - 7.5

Shut-Off Pressure - 55 PSI

Warranty

1 Year

Benefits

- 3 Gallons per Minute
- Self-Priming
- 55 PSI
- Internal Bypass-Low Cycling
- Quiet Operation
- Runs Dry – Thermally Protected
- Built-In Check Valve

Sterling Stainless Steel Bathroom Sink



Specs

Installation Type: Top Mount

Material: Stainless Steel

Gauge: 22 Gauge

Sink Dimensions: 13-1/4" x 10-1/2" x 5"

Drain Size: 1-1/2"

Warranty

1 Year (Limited)

Benefits

Single-sheet 22-gauge stainless-steel construction offers durability

SilentShield sound-absorbing system helps reduce noise and vibration

Mirror finish provides an attractive look

Oval design adds an elegant touch

1-1/2 in. drain opening

Self-rimming or under-counter installation for versatility

Suburban Hot Water Heater



Specs.

Gallon Capacity: 6

Input BTUh/Watts: 12000/1440

Recovery Gals./Hr. (Gas/Electric): 10.2/6.0

Height: 12-11/16"

Width: 12-11/16"

Depth: 19-3/16"

Unit Net Weight (lbs)

Empty: 37.4

Full: 82.6

Warranty

2 Year Limited

Benefits

A 1440 watt Incoloy electric element provides a recovery rate of 6 gallons per hour. For a FAST RECOVERY rate of 16.2 gallons per hour, both gas and electric can be used simultaneously.

VanAir Ventline Bathroom Exhaust Fan



Specs

Fan power: 12-volt DC

100 CFM

Cover color: Smoke

Rough opening size: 6-1/4" diameter

Vent extends above roof:

2-3/8" Closed

3-1/4" Open

Warranty

1 Year

Benefits

- Yields better air circulation than non-powered models, exhausting hot air while trailer or RV remains locked and secure
- Efficient 12-volt centrifugal blower design
- Draws only 1-1/2 amps yet moves 100 CFM - low demand on battery
- Quiet operation
- Easy, one-handed opening and closing of dome
- Translucent cover allows some light through
- Fan uses 12-volt DC power
- Low-profile plastic dome
- Made in the USA

Zip Breakaway Safety Cable

Specs

4' cable
12v Power
Spring clip



Warranty

1 Year (Limited)

Benefits

With the Fastway Zip there are no frayed ends or cables dragging on the ground. The unique coiled cable of the Zip easily stretches to your tow vehicle and clips right on with the included carabiner. There is no looping over and around the trailer tongue to keep the cable out of the way. It is faster, easier and safer than standard breakaway cables. With the Fastway Zip you get:

- A safer, more reliable, legal connection
- Easy attachment with included spring clip
- No more stabbed fingers
- No more frayed or broken cables

Optional Component Guide



Andersen No-Sway Hitch



Specs

Weight - Under 60 lbs

2" Ball Included

Rated at 14,000 lbs GTWR and 1,400 lbs. tongue weight

Warranty

Lifetime Warranty (limited)

Benefits

Unparalleled Sway Control that self-adjusts

So quiet you won't even know it's there!

One pin removal from tow vehicle

Greaseless system –ball and coupler move as one

Easy install –no pry bars needed!

Optional 6" drop/rise adjustable shank available (part #3351)

Patented True Motion-Dampening™ system -drastically reduces bounce

Doubles as standard ball mount for towing without weight distribution

The smoothest ride around - owners are saying they can't believe it!

Progressive Industries EMS-HW30C Surge Protector

Specs

Item Weight -3.2 pounds

Product Dimensions - 10.4 x 5.6 x 4.9 inches

Warranty

Lifetime Warranty (limited)

Benefits

Whenever electrical power falls below 104 volts or rises above 132 volts, the EMS automatically shuts down power to the RV.

Once the electrical power rises above 104-volts, or below the 132-volt level, the time delay indicator flashes for the preset time and then automatically restores power to the RV. Features include: Digital readout, built-in surge fault indication, amperage meter, voltage meter, frequency meter, integrated digital readout, 3-mode surge protection, and reverse polarity protection, open neutral/open ground protection, lost/open neutral protection and AC frequency protection. Factory setting 15 seconds but can be adjusted to a 2 minute 16 seconds (136 seconds) delay for A/C Protection. Frequency Protection (Low <51Hz, High 69HZ>).

Modular design for easy repair, eliminating removal of the unit. Should the software ever change, EMS owners can receive a free upgrade at no cost.



Trojan T-105 and 6v AGM Batteries



Specs

T-105

Voltage 6
Length 10.30 (262)
Width 7.11 (181)
Height 11.07 (281)
Weight 62 (28)
5 HR Rate AH185
10 HR Rate AH207
20 HR Rate AH225
100 HR Rate AH250

AGM

Voltage 6
Length 10.28 (261)
Width 7.08 (180)
Height 10.74 (273)
Weight 65 (29)
5 HR Rate AH154
10 HR Rate AH184
20 HR Rate AH200
100 HR Rate AH221

Warranty

12 Months (T-105 is 18 Months)

Benefits

Trojan's advanced battery designs are long-lasting, clean and built to withstand the challenges of harsh environments and rough terrain. All of Trojan's products are backed by outstanding technical support and customer service. With over 85 years of experience Trojan products are truly powering the planet.

Trojan Hydrolink Watering System



Specs

- (8) 6/12-volt manifolds
- (1) clampless tubing with coupler
- (9) red end caps

Warranty

4 Years

Benefits

- Independent Water Level Indicator – HydroLink comes with an independent, non-mechanical water level indicator that is simple to read: white means the battery needs water and black means the battery has enough water.
- Safety – HydroLink comes with both internal and external flame arrestors, making it the safest watering system in the industry.
- Cost Effective – HydroLink saves valuable time and money by filling a complete set of batteries in less than 30 seconds. With proper watering, HydroLink can maximize battery life.
- Guaranteed – HydroLink is tested and guaranteed to work with your Trojan batteries in the most popular configurations, and it comes with a full 4-year warranty.

TRUMA AquaGo Tankless Water Heater



Specs

Nominal input rate - 20,000 - 60,000 BTU/h (5.9 - 17.6 kW)

Fuel - LP Gas (Propane only)

Fuel inlet pressure - 10.5" - 14" wc (26.2 - 34.9 mbar)

Fuel manifold pressure - 1.3" - 10" wc (3.2 - 24.9 mbar)

Nominal voltage - 12 V DC

Power input - < 2.5 A

Water operating pressure - maximum 65 psi (4.5 bar)

Standard water outlet temperature - 120° F (49° C)

Water volume - 0.35 gallons (1.3 liter)

Weight (approx.) - 34.2 lbs (15.5 kg)

Warranty

1 Year

Benefits

True instant hot water at every tap* - That's Truma luxury

Truma hybrid technology keeps temperature constant - No scalding

Exclusive decalcification technology -

Extends life and maintains performance

Simply open "Easy Drain Lever" - Winterization done

Voyager WiSight Rear View Camera

Specs

7" color LCD monitor
12 volt accessory plug
Rear color camera
Removable sun visor
Suction cup monitor mount
Stainless steel hardware
Non-corrosive camera mounting bracket
WVCMS10B Super CMOS Camera
High performance color optics
Waterproof (IPX 7)
12 Volt DC Power
Viewing angle (Degrees) : D 117° / H 93° / V 66°
Machined aluminum body
Excellent low light and high bright environment performance
14 IR LEDs
Overall Dimensions 3.4"W x 1.7"H x 1.7"D



Warranty

2 Years (Parts) 1 Year (Labor)

Benefits

The Digital Wireless Observation System featuring WI Sight technology far exceeds the performance of any analog wireless observation system on the market.

WI Sight technology digitally locks the Voyager's camera to its monitor so it only communicates with that monitor, ignoring outside signals, eliminating interference.

WiFiRanger RV Pack 2 – WiFi Booster

Specs

WiFi Standards - 802.11 b / g / n / ac (2.4 GHz)
Max Radio Power - 1000 mW (auto adjusts)
Max Range - 1.5 mi
CPU Speed - 600MHz
Memory - 64MB
Weather Proofing - IP67 Outdoor-rated
Mounting - Flat Surface (use adhesive)
Antenna Polarity 360° - Vertical Polarized (upright for proper operation)
Power Method - 24V POE Input from GoAC (port 5)
LAN Ports - 1x Gigabit Ethernet (reserved for power)
Dimensions - 9.7 x 7.5 x 4.5 in
Weight - 15 oz (excluding cable)
Max Power Consumption - 10W
Operating Temperature - -40° to 70° C



Warranty

1 Year

Benefits

A complete network with indoor accessibility and outdoor range, with the SkyPro ready to be mounted directly to a flat surface roof. The SkyPro is equipped with a Flex-guard™ antennas that can bend down to 5" clearance without doing damage to the unit, protecting against trees and other overhangs. Provide a secure, private network for all of your wireless computers and devices with the indoor Core router which also has several LAN ports for hardwiring computers and devices. The SkyPro then brings in otherwise weak WiFi from Hotspots in the area to get your entire network online. The indoor Core is dedicated to providing the secure network and also allows for USB tethering a 3G/4G Aircard or MiFi device. To power the SkyPro and interconnect it with the Core, its 30FT cable needs to run to the inside where the Core is stored, plugging into port 5 of the Core which has Power Over Ethernet (POE) output. Avoid drilling a hole for this cable by routing it to the inside through a refrigerator vent, slide, or engine compartment.

Wilson Mobile 4G Cell Phone Amplifier



Specs

Max Coverage Area - 6 Foot Radius

Frequency - 700MHz, 800MHz, 1900MHz, 1700/2100MHz

Gain - 50dB / 50dB

Impedance - No

Power Requirements - 5 V 2.5 A

Warranty

1 Year

Benefits

The weBoost 470108 Drive 4G-M Mobile Signal Booster Kit is the newest version of the best selling Wilson 460108 Mobile 4G Signal Booster Kit. The Drive 4G-M boosts the 2G, 3G, and 4G LTE networks from all major carriers in the United States and Canada, giving you fewer dropped calls, increased call clarity and the fastest 4G download speeds possible. Unlike less powerful signal boosters, the weBoost Drive 4G-M communicates with your phone wirelessly and does not require a direct connection or for your phone to sit in a cradle. Additionally, because it's wireless, the Drive 4G-M also supports multiple phones and data devices at the same time.

The weBoost 470108 Drive 4G-M's inside coverage area will depend on your existing outside signal strength. In areas where you get a moderate existing outside signal, the Drive 4G-M will fill a normal vehicle with boosted coverage. As the outside signal gets weaker, you may have to keep your phone within about 18 inches from the inside antenna in order to take advantage of the boosted signal.

WineGard Carryout G2

Specs

Color Options: White, Black

Unit Weight: 10 lbs

Diameter: 14.3"

Height (Without Feet): 13.5"

Height (With Feet): 14.2"

Elevation Range: 18-65°

Azimuth: 0 – 416°

UV-Protected Plastic Dome



Warranty

2 Years (Parts) 1 Year (Labor)

Benefits

Compatible with multiple providers

Easily switch providers at power inserter

Powered over coax through power inserter

Permanent & temporary mount options

Fully automatic satellite acquisition

Simple setup

Multi-TV viewing

Ultra-small and compact

WineGard Roadstar Omni-Directional Antenna

Specs

ITEM NUMBER: 24-0169

WINEGARD

MFG NO:RS-3000

WT: 2.70

UPC: 615798400835

WEIGHT: 02.7 LBS



Warranty

2 Years (Parts) 1 Year (Labor)

Benefits

No hand cranking or aiming, the RoadStar antenna is always ready for viewing. This sleek, compact antenna delivers powerful performance and can receive all VHF/UHF/FM frequencies while parked. Installation is a breeze with the new pedestal mount. Package includes on/off power supply, 30' 75 ohm coaxial cable, mounting bracket and hardware. Power supply operates on +12 volt DC and includes +12 VDC receptacle, 2-way splitter for second TV and optional cable input. Can be flush or surface mounted.

Xantrex 2000W Inverter



Specs

PROwatt SW 2000
806-1220
12V
GFCI

Warranty

24 Months

Benefits

600 / 1000 / 2000 watts maximum, 1200 / 2000 / 3000w surge capability
Built-in digital display for DC volts and output power
Built-in USB port
Dual GFCI AC receptacles for safe operation
Heavy duty terminals for trouble-free battery connection
Available ON/OFF remote switch (with ignition lockout)
Meets stringent UL458 regulatory standard

ZAMP Solar Package

Specs

Charge Controller:

Watts - 500

Amps - 30

Solar Panels:

24.85 lbs per panel

58.3" x 26.4" x 1.5" per panel

160watt Power Output per panel

30 Amp Solar Controller



Warranty

1 Year

Benefits

Zamp Solar is the expert in the recreational vehicle solar battery charging industry. Zamp Solar is leading the charge in RV solar charging technology. They have created some of the best and most innovated products available today exclusively for the RV owner.

Made of the same durable and dependable roof mounted solar panels, Zamp Portable Charging Systems will give your customer the ability to charge their batteries easily, affordably, and portably.