

Fontana Exterior Shower - 97022A-5

Installation Instructions:

- ~ Choose a location that is flat and has a minimum of 10" of rear clearance for hose & water connections.
- ~ Using the dotted line on this sheet as a template, cut the opening for the main body of the shower.
- ~ Connect female sprayer hose connection to male collar fitting on the back of the shower using teflon tape.
- ~ Insert shower and predrill the screw holes with a 1/8" drill bit.
- ~ Caulk the mounting flange with suitable weather resistant, flexible sealant material.
- ~ Drive in #8 flat head screws until secure.
- ~ Connect the faucet set to the on-board water system.
- ~ Attach the hose and shower head.

Specifications:

- ~ Designed for use in a pressure regulated, portable water system with a maximum operating pressure of 40psi.
- ~ Maximum flow rate with the faucets fully opened - 2.5GPM.
- ~ DO NOT ALLOW TO FREEZE.
- ~ Do not connect directly to a high pressure residential water supply.

Replacement Parts:

White Shower Head	97022-001
Hose	97020-002
Hose Washer	97020-003
Vacuum Breaker	97022-006
O-Ring Washer	97020-007
Chrome Faucet Set	97020-008
White Faucet Set	97022-008
Slide Latch	97020-009
Seal Collar	97020-080



By ITC

230 E. Lakewood Blvd
PO Box 8338
Holland, MI 49422-8338
Phone: 1.888.871.8860
E-Mail: sales@itc-us.com
Website: www.itc-us.com



97022-A-5
Latching Shower

Common repair parts:



97022-001



97022-008



97020-080