


Your Search: Name : LTX M/S



LTX® M/S

Light Truck, SUV/Crossover



A long-time consumer favorite, MICHELIN® LTX® M/S tires offer long tread life and true all-season traction capabilities.

Benefits of This Tire:

- Up to 15% Better Snow Traction Than the Competition¹
- Three-Steel-Belt Durability
- Wears Evenly, Long Lasting

Average User Rating:



Michelin Performance Ratings:

Wear Life 8/10	Fuel Efficiency 8/10	Off Road 7/10	Braking 7/10	Comfort 8/10

Tire Warranties:



Warranties



60,000 Mile Manufacturer's Treadwear Limited Warranty
LTX® M/S tires carry an additional 60,000 mile limited warranty for treadwear or mileage.

Available on:
LTX® M/S
Speed Rating [H, R, S, T]



Standard Limited Warranty (All Michelin® Tires)
All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details.

TechSpecs

Part #	Tire Size	Load Index	Speed Rating	Sidewall	Mileage Warranty	UTQG Treadwear, Traction, Temp	Rim Width Range (Min / Max)	Section Width (On Measuring Rim Width)	OE Code	Overall Diameter	Revs Per Mile	Tread Depth (in 32nds)	Max Load, Single (@PSI)	Max Load, Dual (@PSI)	Tire Weight
23526	P215/75R15	100	S	ORWL	60,000 Mile	500, A, B	5.5" - 7"	8.6" on 6"		27.6	754	13	1584@35	@	28.42
48079	P225/70R15	100	S	ORWL	60,000 Mile	500, A, B	6" - 7.5"	9" on 6.5"	MA	27.4	765	13	1594@35	@	28.55
76017	P225/75R15	102	S	ORWL	60,000 Mile	500, A, B	6" - 7.5"	9" on 6"		28.3	741	13	1703@35	@	29.41
97679	P235/70R15	102	S	ORWL	60,000 Mile	500, A, B	6" - 8"	9.4" on 7"		27.9	746	13	1724@35	@	29.34
78868	LT235/75R15/C	104	R	ORWL	60,000 Mile	.	6" - 7"	9.5" on 6.5"		28.8	727	13	1985@50	1820@50	30.36
09418	30x9.50R15/C	104	R	ORWL	60,000 Mile	.	6.5" - 8.5"	9.6" on 7"		29.6	706	15	1985@50	@	38.36
24798	31x10.50R15/C	109	R	ORWL	60,000 Mile	.	7" - 9"	11.1" on 9"		30.8	679	15	2270@50	@	43.87
60041	P215/70R16	99	S	ORWL	60,000 Mile	500, A, B	5.5" - 7"	8.7" on 6.5"		27.8	755	13	1554@35	@	29.17
65141	LT225/75R16/E	115	R	ORWL	60,000 Mile	.	6" - 7"	8.8" on 6"	F	29.4	709	15	2680@80	2470@80	39.24
25516	LT225/75R16/E	115	R	BSW	60,000 Mile	.	6" - 7"	8.8" on 6"	F	29.4	709	15	2680@80	2470@80	38.62
76721	P235/70R16/XL	107	S	ORWL	60,000 Mile	500, A, B	6" - 8"	9.6" on 7"	F	29.1	717	13	1954@41	@	32.65
22606	LT245/75R16/E	120	R	BSW	60,000 Mile	.	6.5" - 8"	9.8" on 7"	DC	30.7	681	15	3042@80	2778@80	42.33
43428	P275/70R16	114	S	BSW	60,000 Mile	500, A, B	7" - 10"	11.1" on 8"	L, T	31.3	666	12	2365@35	@	40.19
98835	P275/70R16	114	H	BSW	60,000 Mile	440, A, A	7" - 10"	11.1" on 8"	T	31.3	666	12	2365@44	@	38.69
35551	P245/65R17	105	T	BSW	60,000 Mile	440, A, B	7" - 8.5"	9.6" on 7"	HO	29.7	700	11	1854@44	@	33.27
13192	P245/60R18	104	T	BSW	60,000 Mile	440, A, B	7" - 8.5"	9.8" on 7"	HO	29.6	703	11	1804@44	@	32.67

1Compared against Bridgestone® Dueler™ H/T, Goodyear® Fortera® featuring TripleTred Technology™, and Goodyear® Wrangler® featuring SilentArmor Technology™.
 2Using four LT265/75R16/E/TT tires inflated at 80 psi.

OE Code [Original Equipment Key]: DC = DaimlerChrysler, F = Ford, HO = Honda, I = Infiniti, L = Lexus, MA = Mazda, N = Nissan, T = Toyota

* Passenger sizes used in Light Truck/SUV applications have reduced load capacity. This will differ from the maximum load branded on the tire sidewall.

Government UTQG Ratings do not apply to light truck sized tires.

XL = Extra Load

>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the sectionheight (affecting overall diameter), and +/-4% of the section width.

>> Sectionwidth varies approximately 0.2" (5mm) for every 0.5" change in rim width.

>> Tread patterns are often tuned to accomodate different tire widths. Tires for a particular dimension of a given tireline may vary in appearance from the tire shown in the photograph.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

S-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112

Inflation Increase (psi) 0.0 1.0 2.0

Load Capacity (% of max.) 100 100 100

T-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112 118

Inflation Increase (psi) 0.0 1.0 2.0 3.0

Load Capacity (% of max.) 100 100 100 100

H-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112 118 124 130

Inflation Increase (psi) 0.0 1.0 2.0 3.0 4.0 5.0

Load Capacity (% of max.) 100 100 100 100 100 100